

## Especificaciones Generales de los Hules SBR

### Hules SBR en Frío

Grado	Emul	Estabilizador	Estireno %	MML 1+4
1500	RA	S	23.5	52
1502*	MA	NS	23.5	52
1502L	MA	NS	23.5	41
1503	FA	NS	23.5	51
1507	MA	NS	23.5	36
1510	FA	NS	23.5	32
1551	RA	NS	23.5	52
8107	FA	NS	5.5	22
8113*	RA	NS	23.5	115

\*1502 and 8113 also available in crumb form.

### Hules SBR en Frío con aceite

Grado	Emul	Estabilizador	Estireno %	Aceite Tipo/Partes	MML 1+4
1712L	MA	S	23.5	HiAr 37.5	35
1712	MA	S	23.5	HiAr 37.5	45
1712H	MA	S	23.5	HiAr 37.5	52
1713	MA	NS	23.5	Naph 50	41
1721	MA	S	40.5	HiAr 37.5	54
1778	MA	NS	23.5	Naph 37.5	53
8401	MA	S	39.5	Traxol 37.5	55



**Milagro Rubber Co.**

3355 Bee Cave Rd. Suite 304  
Austin, TX 78746

+1 512 330 9352

[www.e-milagro.com](http://www.e-milagro.com)

[info@e-milagro.com](mailto:info@e-milagro.com)

### Oleoextendido Manchante

Grado	Emul	Aceite*		Negro*		CML 1+4
		Tipo/Partes		Tipo/Partes		
1606	RA	HiAr	10	N330	52	51
1606L	RA	HiAr	10	N330	52	47
1847	MA	HiAr	50	N339	75	40
1848	MA	HiAr	62.5	N339	82.5	35
1850	MA	HiAr	50	N330	75	40
1851	MA	HiAr	62.5	N330	82.5	36
4684	MA	HiAr	10	N234	52	49
4689	MA	HiAr	12	N550	55	48

### Oleoextendido No Manchante

Grado	Emul	Aceite*		Negro*		CML 1+4
		Tipo/Partes		Tipo/Partes		
1815	MA	Naph	50	N330	75	47
1815L	MA	Naph	50	N330	75	36
1821	MA	Naph	37.5	N550	80	43

### Tipos de Masterbatch con micro Negro de Humo

Grado	Emul	Aceite*		Negro*		CML 1+4
		Tipo/Partes		Tipo/Partes		
1605	FA	*		N550	50	60
4681	MA	*		N326	50	49



**Milagro Rubber Co.**

3355 Bee Cave Rd. Suite 304  
Austin, TX 78746

+1 512 330 9352

[www.e-milagro.com](http://www.e-milagro.com)

[info@e-milagro.com](mailto:info@e-milagro.com)